US009409457B2

(12) **United States Patent**
Gielisch et al.

(10) **Patent No.: US 9,409,457 B2**
(45) **Date of Patent: Aug. 9, 2016**

(54) **INDEPENDENT SUSPENSION OF A WHEEL OF A TWO-TRACK VEHICLE WITH A SCISSOR-TYPE ARM AND A SPRING ELEMENT**

(71) Applicant: **Bayerische Motoren Werke Aktiengesellschaft**, Munich (DE)

(72) Inventors: **Sebastian Gielisch**, Unterschleissheim (DE); **Martin Ladstaetter**, Bergkirchen (DE); **Alfred Pruckner**, Munich (DE); **Dirk Schlichte**, Munich (DE); **Roland Koenig**, Habach (DE)

(73) Assignee: **Bayerische Motoren Werke Aktiengesellschaft**, Munich (DE)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/666,442**

(22) Filed: **Mar. 24, 2015**

(65) **Prior Publication Data**

US 2015/0191064 A1 Jul. 9, 2015

Related U.S. Application Data

(63) Continuation of application No. PCT/EP2013/066225, filed on Aug. 1, 2013.

(30) **Foreign Application Priority Data**

Sep. 25, 2012 (DE) 10 2012 217 271

(51) **Int. Cl.**
B60G 3/20 (2006.01)
B60G 3/14 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC ***B60G 3/20*** (2013.01); ***B60G 3/145*** (2013.01); ***B60G 3/185*** (2013.01); ***B60G 3/22*** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC B60G 3/20; B60G 15/06; B60G 7/00; B60G 3/145; B60G 3/185; B60G 11/14; B60G 3/22; B60G 2200/14; B60G 2200/46; B60G 2200/446; B60G 2202/30; B60G 2204/414; B60G 2200/13; B60G 2204/421; B60G 2204/30
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,087,115 A * 5/1978 Earle B60G 3/12 267/221
5,620,173 A 4/1997 Yang
(Continued)

FOREIGN PATENT DOCUMENTS

DE 42 03 057 A1 8/1993
DE 10 2010 029 032 A1 11/2011
(Continued)

OTHER PUBLICATIONS

International Search Report (PCT/ISA/210) dated Feb. 4, 2014 with English translation (seven pages).
(Continued)

Primary Examiner — Drew Brown
(74) *Attorney, Agent, or Firm* — Crowell & Moring LLP

(57) **ABSTRACT**

An independent suspension of a wheel of a two-track vehicle includes a trailing arm, one of the end portions of which is hinged to a vehicle body of the vehicle and the other end portion of which supports a wheel carrier. A scissor-type arm is hinged to the trailing arm and guides the trailing arm relative to the vehicle body. A spring element supports the trailing arm relative to the vehicle body. The spring element is arranged on the trailing arm in the region of the hinge point of the scissor-type arm to the trailing arm when seen in the direction of the vehicle longitudinal axis.

15 Claims, 16 Drawing Sheets